



ASI HYDRAULICS POWER UNITS
STANDARD LOW NOISE

Standard Features:

- Vertically Mounted
- Rear Motor Mounted Cooler
- UL Controls
- Low Noise

Typical Applications:

- Line Boring
- Portable Boring
- Shovel & Drag Line Repair
- Large Pipe Prep
- Industrial: Presses, Press-breaks, Forming Tools & Chippers



Specifications

Frame:	Powder coated or painted finish
Current Draw:	32 AMPS
Oil Capacity:	30 gallons AW32 or AW46
Pressure:	Factory set at 1800 PSI
Flow:	Multiple flows available
Operating Temp:	110°F / 43.3°C - 175°F / 79.4°C
Sound Level:	62 dB at full flow and operation <i>(reading taken in normal shop surroundings)</i>
Electrical:	UL/CUL listed NEMA 4 electrical controls - 440, 460, 480, VAC input power (50/60 hz 3-phase) (460 standard)
Input Power:	380, 460, 480 VAC Input Power (50/60 hz 3-phase) (460 standard)
Light Indicator:	Over Temp. / Low Oil Light
Pendant:	Pendant cable of 12 ft plus 50 ft. extension
Wheel/Base:	Removable mobile base with non-marring casters
Lifting System:	5 point lifting system
Filter:	10 Micron
Heat Exchanger:	24vdc fan with digital read out
Gear Pump:	Helical cut ultra quiet hydraulic gear pump.
Dimensions:	46.5" H x 25" W x 24" L w/o Base 52.5" H x 26" W x 34.5" L w/ Base
Weight:	850 lbs with oil

12.02.2020